



# RoadStar 1500

Mobile Asphalt Batch Plant



Quality Engineered  
Excellence Since 1911



# RoadStar 1500 Mobile Asphalt Batch Plant - 120tph\*

- Fully mobile road towable units
- Minimum foundations
- Fast on-site erection
- Factory pre-wired & fully tested
- Inverter controlled exhaust fan
- Dust filter emissions less than 20mg/Nm<sup>3</sup>

The Parker RoadStar 1500 is a highly efficient mobile asphalt mixing plant capable of producing a wide range of mixes to world standards. The three main units of the plant - cold feed, aggregate dryer and mixing section - are all road towable, and on arrival to site can be brought quickly into operation.

## Mobile Cold Feed Unit (3 or 4 hoppers) + Sand Vibrator



Compact road towable cold feed unit with built in collecting/dryer feed conveyor. Direct drive AC motor/gear units and inverter give high reliability whilst a high turndown ratio provides accurate control over the feed rate. Three or four bin options are available.

## RoadStar 1500 Specification

|  | Units             |                      |
|--|-------------------|----------------------|
| <b>Cold Feed</b>                                       |                   |                      |
| Hopper Capacity (heaped)                               | m <sup>3</sup>    | 10.0                 |
| Hopper Loading Width                                   | m                 | 3.0                  |
| Belt Feeder Length                                     | m                 | 1.7                  |
| Belt Width   | mm                | 500                  |
| Belt Feeder Drive                                      | kW                | 2.2                  |
| Vibrator Fitted to Sand Hopper                         |                   | YES                  |
| Collecting Conveyor Width                              | mm                | 500                  |
| Collecting Conveyor Drive                              | kW                | 5.5                  |
| <b>Aggregate Dryer</b>                                 |                   |                      |
| Dryer Drum Diameter                                    | m                 | 1.8                  |
| Dryer Drum Length                                      | m                 | 7.0                  |
| Dryer Drive  | kW                | 30.0                 |
| Dryer Capacity   | t/h               | 120                  |
| <b>Air Volume</b>                                      |                   |                      |
| Dryer  | m <sup>3</sup> /h | 41,885               |
| Mixing Section   | m <sup>3</sup> /h | 7,850                |
| Total  | m <sup>3</sup> /h | 49,735               |
| <b>Hot Stone Elevator, Screen &amp; Mixing Section</b> |                   |                      |
| Elevator Capacity                                      | t/h               | 130                  |
| Drive  | kW                | 7.5                  |
| Screen Decks   | No.               | 2 (4 size + rejects) |
| Screen Length  | m                 | 4.0                  |
| Screen Width   | m                 | 1.5                  |
| Screen Drive   | kW                | 7.5                  |
| Hot Storage Capacity                                   | t                 | 12                   |
| Hot Storage Bins                                       | No.               | 4                    |
| Batch Elevator Capacity                                | t/h               | 130                  |
| Batch Elevator Drive                                   | kW                | 7.5                  |
| Aggregate Weigh Hopper Capacity                        | kg                | 1500                 |
| Bitumen Weigh Hopper Capacity                          | kg                | 295                  |
| Filler Weigh Hopper Capacity                           | kg                | 320                  |
| Paddle Mixer Capacity                                  | kg                | 1500                 |
| Paddle Mixer Drive                                     | kW                | 2 x 18.5             |

## Mobile Aggregate Dryer & Chassis Mounted Primary Dust



Road towable unit with high efficiency internal lifter design. Optional Insulated and clad drum. Fitted with advanced multi fuel burner. Chassis mounted multi-bank cyclone unit for primary dust collection.

## Mobile Mixing Section & Control System



Compact, low level, towable unit with integral vertical hot stone elevator, which folds down for travelling. Heavy duty screen with a fully sealed dust housing. Batch weigh hoppers for aggregate, bitumen and filler are all load cell mounted. The RoadStar has a fully synchronised twin shaft, direct motor drive, high efficiency paddle mixer, hard wearing abrasive resistant liner plates, paddle arms and tips are standard. Material discharge is either into a mixed material storage unit or direct into truck. Dependant on location the RoadStar 1500 is available with optional bag filter and fan unit for secondary dust collection achieving less than 20mg/m<sup>3</sup>. Control system - insulated & clad control cabin with a range of advanced control options from keypad to PC based, fully automatic systems.

\*Plant capacity is based on 3% moisture content of feed aggregate with 0.5% residual moisture content of mixed materials, dryer discharge temperature of 160°C, ambient temperature 15°C at altitude 150m above sea level, aggregate bulk density average 1600kg/m<sup>3</sup>, 5% bitumen content, 45 second weigh/mix cycle at 100% plant utilisation.

Note: Bag Filter Specification listed separated

**Parker Plant Limited, Viaduct Works, Canon Street, Leicester, LE4 6GH, United Kingdom**

**T: +44 (0) 116 266 5999 F: +44 (0) 116 261 0812 W: www.parkerplant.com E: sales@parkerplant.com**

All reasonable steps have been taken to ensure the accuracy of this publication. However, due to our policy of continual product development, Parker Plant Limited reserve the right to change details without prior notice. All machines supplied in accordance with our standard conditions. Illustrations and photos may show optional equipment. All rights reserved.