



Transmix 2300

**Modular Free Standing
Asphalt Plant**



**Quality Engineered
Excellence Since 1911**

Transmix 2300 - 200tph Asphalt Batch Plant



- Modular construction - plant designed to fit in standard containers
- Fast on-site erection and dismantling
- Factory pre-wired & fully tested
- Inverter controlled exhaust fan
- High efficiency burner
- Electronic loadcell weighing
- Microprocessor controls, housed in remote control cabin
- Dust filter with emissions less than 20mg/m³

Aggregate Feed Unit

Compact, robust, modular 4 hopper cold feed unit with highly accurate AC variable speed inverter controlled direct drive motor/gear units.



Aggregate Dryer

Easily transported aggregate dryer with advanced design of internal lifters optimising thermal efficiency for maximum heat transfer. Choice of multi-fuel burners. Nylon support & thrust rollers reduce wear, vibration and noise.



Screening, Mixing & Hot Storage Tower



The quick erect modular tower features a heavy duty aggregate screen within a fully sealed dust housing and ease of maintenance access with stairways & platforms at all levels.

Discharge to truck or mixed material storage facility.

All main sections of the plant are designed to be free standing with no tension or uplift to the slab bases. No holding down bolts are required. Hard standing is essential to accommodate the maximum pressure transmitted by the units of 0.35N/mm² (35.7 tonne/m²).

The TransMix 2300 has been designed to fit standard open top ISO containers for ease of shipment.

Control system: insulated & clad control cabin with a range of advanced control options from keypad to PC based, fully automatic systems, with fully programmable recipe storage.

Specification

	Units	
Aggregate Feed Unit		
Feed Hopper Capacity (Each) Heaped	m ³	10
Feed Hopper Loading Width	m	3
Feed Hopper Loading Height	m	3.45
Belt Feeder Length	m	1.5
Belt Width	mm	600
Collecting Conveyor Belt Width	mm	650
Aggregate Dryer		
Dryer Drum Diameter	m	2.2
Dryer Drum Length	m	8
Air Volume		
Dryer	m ³ /h	54,000
Mixing Section	m ³ /h	10,000
Total	m ³ /h	64,000
Screen & Mixing Section		
Elevator Capacity	t/h	220
Hot Storage Capacity	t	25
Hot Storage Bins	No.	4, 5 or 6
Aggregate Weigh Hopper Capacity	kg	2750
Bitumen Weigh Hopper Capacity	kg	450
Filler Weigh Hopper Capacity	kg	600
Paddle Mixer Capacity	kg	2750
Paddle Mixer Drive	kW	2 x 30

*Plant capacity is based on a temperature of 150°C output from mixer. Average moisture content 3%, including 3% filler and 5% bitumen in the mix. Mixer capacity of 2250 Kg per batch, 45 second weigh/mix cycle, 80 batches/hr

Note: Bag Filter Specification listed separated

Parker Plant Limited, Viaduct Works, Canon Street, Leicester, LE4 6GH, United Kingdom
T: +44 (0) 116 266 5999 F: +44 (0) 116 261 0812 W: www.parkerplant.com E: sales@parkerplant.com

All reasonable steps have been taken to ensure the accuracy of this publication. However, due to our policy of continual product development, Parker Plant Limited reserve the right to change details without prior notice. All machines supplied in accordance with our standard conditions. Illustrations and photos may show optional equipment. All rights reserved.