



T8048

Tracked Conveyor

Quality Engineered
Excellence Since 1911



Parker T8048 Tracked Conveyor 24.4m x 1.2m (80' x 48")



The Parker T8048 tracked conveyor offers superior stockpiling capacity and minimises on-site material handling costs. Designed for ease of mobility on-site, it is manufactured with a highly robust chassis for optimal strength in difficult working conditions, such as those within a quarry plant.

Input and stockpile height can be easily adjusted in order to achieve the maximum stockpile height and minimum dust creation and material impact. The hydraulic folding conveyor allows for fast efficient road transportation and rapid set-up time.

- Robust and durable chassis
- Hydraulically folding for rapid on-site setup
- Hydraulically adjustable input & stockpile height
- Thermostatically controlled hydraulic oil cooler fitted as standard
- Remote control for easy tracking mobility

Options:

Dust Covers	Electric Drive
Dust Suppression	Chevron Belt
Extended Feed Hopper	Discharge Dust Chute
Wear Resistant Feed Hopper Lining	Full Radio Remote Control

	Units	T8048
	mm	12040
	ft / ins	39' 6"
	mm	2350
	ft / ins	7' 8"
	mm	2590
	ft / ins	8' 5"
	kg	13,000
	lbs	28,660

Belt Length	24400mm (80')
Belt Width	1200mm (48")
Belt Spec	3 Ply
Stockpile Height	10038 mm (32' 9")
Maximum Angle	24°
Engine	Deutz TD 2011 - Tier 3
Power Output	49 kW (66 hp)
Diesel Tank	205L Capacity (45gallon [US])

Parker Plant Limited, Viaduct Works, Canon Street, Leicester, LE4 6GH, United Kingdom

T: +44 (0) 116 266 5999 F: +44 (0) 116 266 4422 W: www.parkerplant.com E: sales@parkerplant.com

All reasonable steps have been taken to ensure the accuracy of this publication. However, due to our policy of continual product development, Parker Plant Limited reserve the right to change details without prior notice. All machines supplied in accordance with our standard conditions. Illustrations and photos may show optional equipment.