



# TR0750

## Tracked RockRanger Jaw Crusher



Check Out Online



Quality Engineered  
Excellence Since 1911



# Parker TR0750 Tracked Jaw 700mm x 500mm



The compact TR0750 is ideal for primary crushing in small quarrying operations or for demolition contractors where setup speed and operating space is restricted.

With many outstanding and user-friendly features as standard this reliable, robust and extremely productive unit providing a high quality consistent end product.

- Robust and durable jaw crusher featuring rapid setup times
- High throughput capacity and large reduction rates
- Advanced electronic control system interface
- Easily accessible maintenance and service points
- Efficient powerpack designed for low operating cost
- Global aftersales service, support and spare parts supply

## Options:

Product Conveyor Weigh Scale	Hydraulic Breaker Arm (Bolted)
Wear Resistant Steel Hopper Liners	Overband Magnet
Hydraulically locking hopper wings	Side Discharge Conveyor
Feed Hopper Extension Wings	Undercrusher Deflector Plate
Centralised Lubrication System	Increased Fuel Tank Capacity
Product Conveyor Dust Covers	Remote Diesel Fill Pump
Water Pump (Electric)	Arctic (-20°C) or Desert (50°C) Pack
Engine Bay Fire Suppression	Remote Located Service Centre

	Units	TR0750
	mm	10700
	ft / ins	35' 1"
	mm	2500
	ft / ins	8' 2"
	mm	3000
	ft / ins	9' 10"
	kg	24,000
	lbs	52,900

Feed Hopper Capacity	3.25m <sup>3</sup> (4.25yd <sup>3</sup> )
Loading Height	3000mm (9' 10")
Grizzly Bar Aperture	50mm (2")
Jaw Feed Opening	700mm x 500mm (28" x 20")
Maximum Feed Size	420mm
Setting Range	40-120mm (1.5"-5")
Drive Type	Hydraulic power supplied via PTO
Product Conveyor Width	800mm (31.5")
Forward Stockpile Height	2610mm (103")
Side Discharge Conveyor Width	500mm (20")
Side Discharge Height	1740mm (69")

**Parker Plant Limited, Viaduct Works, Canon Street, Leicester, LE4 6GH, United Kingdom**

**T: +44 (0) 116 266 5999 F: +44 (0) 116 261 0812 W: www.parkerplant.com E: sales@parkerplant.com**

All reasonable steps have been taken to ensure the accuracy of this publication. However, due to our policy of continual product development, Parker Plant Limited reserve the right to change details without prior notice. All machines supplied in accordance with our standard conditions. Illustrations and photos may show optional equipment. All rights reserved.